

Sela

Making the highest quality phone in the world

Basic phone with flash, Redial & Paper Faceplate



Features

1. Battery free solution
2. Cellular phone RFI noise immunity
3. Last number redial
4. Flash for behind PBX uses
5. Ringer volume Hi-Low adjustable
6. Desk/Wall mountable

MODEL: KT-9290


PLEASE READ OPERATION MANUAL BEFORE USING YOUR
NEW TELEPHONE AND KEEP IT FOR FURTHER REFERENCE.

IMPORTANT SAFETY INSTRUCTIONS


When using your telephone equipment, basic safety precautions should always be followed to reduce the risk of fire, electrical shock and injury to persons.

1. Read and understand all directions.
2. Follow all warnings and instructions.
3. Unplug this product from the wall outlet before cleaning by damp cloth .
4. Do not use this product near water.
5. Do not place this product on an unstable cart, stand, or table. The product may fall, causing serious damage to the product.
6. Do not allow anything to rest on the telephone cord. Do not locate this product where the cord will be abused by persons walking on it.
7. Never put foreign objects of any kind into the product as they may touch dangerous voltage points or short out parts that could result in a risk of fire or electrical shock.
8. To reduce the risk of electrical shock, do not disassemble this Product, Take it to a qualified service person if service or repair work is required. incorrect opening and reassembly may cause risk.
9. Adjust only the controls that are covered by the operating instructions. Improper adjustment of controls may result in damage that could require extensive work by a qualified technician.
10. Refer servicing to qualified service personnel if the following should occur:
 - When the phone line or plug is damaged or frayed.
 - If liquid has been spilled into the product.
 - If the product has been exposed to rain or water.
 - If the product does not operate normally by following operating instructions.
 - If the product has been dropped or the cabinet has been damaged.
 - If the product exhibits a distinct change in performance.
11. Avoid using a telephone during an electrical storm. There may be a risk of electrical shock from lightning.
12. Do not use the telephone in the vicinity of a gas leak.
13. The handset receiver may retain dangerous materials such as metallic pins and staples because the receiver is magnetic.

LOCATION AND FUNCTION OF CONTROLS




- ① Paper Faceplate.....To write telephone number or memo.
- ② Flash.....To use behind PBX system.
- ③ Redial.....Press to dial the last dialed number.
- ④ Dialing Key(0-9,*,#).....Dial phone numbers and extensions.
- ⑤ Handset Coil Cord.....Connect the handset to the base unit.
- ⑥ Handset.....For speaking & listening.
- ⑦ Handset Hook Guide.....Turn 180 degrees to hang up the handset when the phone is mounted on the wall.
- ⑧ Hook On/Off Switch.....Press to end the call.
- ⑨ Line Cord Jack.....Connect telephone set to wall Jack.
- ⑩ Ringer HI/LOW Adjustable.....To adjust the ringer volume.



INSTALLATION

- 1.Connect one end of handset coil cord into the jack of the handset, connect the other end into the jack in the base unit.
- 2.Plug one end of phone line into the line jack of the base unit ,connect the other end into the wall jack.



OPERATION

- 1.Make a call: Pick up the handset to get dial tone and dial the number.
- 2.Answer the call: Pick up the handset to answer the call.
- 3.End the call: Hang up the handset to end the call.
- 4.Redial: Pick up the handset, press **[REDIAL]** to redial the last dialed number.
- 5.Flash: To use for line transfer or intercom behind the PBX systems.
- 6.Ringer Volume Adjustable: Slide the **[RINGER VOLUME]** switch to adjust the ringer volume.

TROUBLE SHOOTING GUIDE

| SYMPTOM | CAUSE AND REMEDY |
|--|--|
| Phone does not working | Is the phone cord connected properly both in wall jack and in the base unit? |
| Ringer volume is too low | Is ringer volume set on low? |
| Phone can receive but can not make calls | The phone has to meet the local telecom dialing mode(Tone only) |